



GRAB MORE

AF3000



**FLOORING
ADHESIVE**

**CONTRACTOR.
ARE YOU READY?**

THE NEW GLADIATOR REVEALED

ARDEX AF 3000

A LOW SOLVENT CONTENT, HIGH QUALITY, SYNTHETIC RESIN/RUBBER ADHESIVE WITH EXCELLENT WET GRAB AND RAPID STRENGTH DEVELOPMENT. ARDEX AF 3000 SECURES A VARIETY OF FLOORCOVERINGS ONTO CONCRETE, SAND/CEMENT SCREEDS, LATEX AND WATER-BASED LEVELLING AND SMOOTHING COMPOUNDS, TERRAZZO, PLYWOOD, HARDBOARD, FLOORING GRADE CHIPBOARD, THERMO-PLASTIC TILES AND QUARRY TILES.

- ★ Superb on-site performance
- ★ Excellent wet grab
- ★ Easy application
- ★ Up to 20 minutes open time
- ★ Rapid strength development



- ★ ARDEX AF 3000 secures textile floorcoverings including fibre bonded carpets, needle punch, latex and rubber foam backed, hessian, felt and resin backed carpets.



- ★ ARDEX AF 3000 can be used for linoleum and some PVC-based tiles and sheet.
- ★ Suitable for use with underfloor heating systems



ARDEX AF 3000. A weapon of war for the flooring contractor, domineering, aggressive and powerful - a true warrior king. Fights hard with **rapid strength development.**

Leaves nothing in its path, extinguishing the opposition with its **excellent on-site performance.**



ARDEX AF 3000 is a great product. Nothing better exists in the market place. I used ARDEX AF 3000 at Northumbria University with superb results.



Darren Cooper, Newcastle Flooring Co. Ltd



Extremely impressed. I have used it at the first stage of the Jury's Inn. I will definitely be buying ARDEX AF 3000 for the next phase of the hotel.



Simon Ward, Highglade Flooring

ARDEX AF 3000 MEETS THE ULTIMATE CHALLENGE

- No other contender can match the superb on-site performance and excellent wet grab of ARDEX AF 3000
- Rapid strength development coupled with ease of use, means it is fast winning approval among professional flooring contractors
- Add to this the versatility to adhere to carpets, linoleum, PVC sheet and tile, giving you a superb multi-purpose flooring adhesive

Contractor. Are you ready?

Available now from your ARDEX stockist.

Visit ARDEX online: www.ardex.co.uk to find out more.

ARDEX AF 3000 Characteristics

Colour	Cream/Yellow	Open Time	Up to 20 minutes, depending on temperature, humidity and absorbency of sub-floor
Consistency	Viscous Liquid	Storage	Store between 5°C and 30°C
Coverage	Approximately 3m ² per litre depending on the condition and absorbency of the sub-floor and the application technique	Shelf Life	12 months in unopened containers stored under good conditions
		Packaging	15 litre



ARDEX UK LIMITED
Homefield Road Haverhill Suffolk CB9 8QP United Kingdom
Telephone: 01440 714939 Fax: 01440 716667
Email: info@ardex.co.uk **ARDEX online:** www.ardex.co.uk



SYSTEMARDEX
PREMIUM PERFORMANCE